

Serial No. 10/751,057

Page 2

Amendments to the Claims:

This listing of the claims will replace all prior versions, and listings, of claims in the application:

1. (previously amended) A method of camping in a device of a communication system comprising:
 - camping on a first carrier frequency;
 - receiving, over the first carrier frequency, a frequency redirection message directing the device to camp on a second carrier frequency;
 - receiving a notification, on a control channel associated with the second carrier frequency, of the start of a data session on the second carrier frequency;
 - and
 - camping on a second carrier frequency.
2. (previously amended) The method according to claim 1, further comprising camping on the first carrier frequency after the data session has been received on the second carrier frequency.
3. (Original) The method according to claim 1, wherein the frequency redirection message is sent on a broadcast channel of the first carrier frequency.

Serial No. 10/751,057

Page 3

4. (Original) The method according to claim 2, wherein the frequency redirection message is a broadcast data service redirection message.
5. (Original) The method according to claim 4, wherein the frequency redirection message includes the parameters of a radio configuration for the second carrier frequency.
6. (currently amended) The method according to claim 4, wherein the parameters of a radio configuration for the second carrier frequency are stored ~~store~~ in a memory of the device.
7. (Original) The method according to claim 1, wherein the frequency redirection message is sent on a broadcast control channel (BCCH) of the first carrier frequency the device is camped on.
8. (previously amended) The method according to claim 1, wherein the control channel associated with the second carrier frequency is a multicast control channel (MCCH) on which the device is camped.
9. (previously amended) The method according to claim 1, wherein receiving a notification, on a multicast control channel (MCCH) associated with the second

Serial No. 10/751,057

Page 4

carrier frequency, of the start of the data session on the second carrier frequency receiving the notification prior to the start of the data session.

10. (Original) The method according to claim 2, further comprising:
determining a configuration associated with the second carrier frequency in accordance with receiving a broadcast data session; and
configuring the device to receive the broadcast data session in accordance with the determined configuration.
11. (Original) The method according to claim 10, further comprising receiving the broadcast data session on the second carrier frequency.
12. (Original) The method according to claim 10, further comprising:
receiving a first broadcast data set on the first frequency; and
simultaneously receiving a second broadcast data set on the second frequency.
13. (Original) A method of camping in a multiple frequency communication system, comprising:
transmitting an information message for a data session redirection to a second carrier frequency on a first carrier frequency, on which at least one mobile station is camped; and

Serial No. 10/751,057

Page 5

sending a start of data session notification message on a plurality of control channels, at least one of which is associated with the second carrier frequency.

14. (Original) The method according to claim 13, wherein at least one of the plurality of control channels is a multicast control channel (MCCH).

15. (previously amended) The method according to claim 13, wherein the start of the data session notification message is sent prior to the start of the data session.

16. (previously amended) A method for camping in a multi-frequency wireless communication system, comprising:

broadcasting over a BCCH to a mobile station on a first frequency semi-static information for a service redirection for a data session;

broadcasting over a plurality of multicast control channels (MCCH's), a notification of the data session, prior to the start of the data session over the first frequency; and

camping on a second frequency associated with at least one MCCH of the plurality of MCCH's.

Serial No. 10/751,057

Page 6

17. (New) A method of camping in a device of a communication system comprising:

camping on a first carrier frequency;

receiving, over the first carrier frequency, a frequency redirection message directing the device to camp on a second carrier frequency;

determining a configuration associated with the second carrier frequency in accordance with receiving a broadcast data session;

configuring the device to receive the broadcast data session in accordance with the determined configuration;

camping on a second carrier frequency;

receiving a notification, on a control channel associated with the second carrier frequency, of the start of a data session on the second carrier frequency;

receiving a first broadcast data set on the first frequency;

simultaneously receiving a second broadcast data set on the second frequency;

and

camping on the first carrier frequency after the data session has been received on the second carrier frequency.